OUTDOOR 'WIND-RATED' HOARDING CONFIGURATIONS

- Completely free-standing – no fixings or ground penetrations required and no property damage caused
- Multiple height and wind capabilities available: Up to 4mH or 122.4Kph (wind speed capability)
- Both Single and Double stack configurations available to meet site-specific wind requirements
- Single Stack option has a footprint of only 46cm deep
- Double Stack option has a footprint of only 92cm deep
- Propriety 'Support Post' available to support both options



SINGLE STACK CONFIGURATION

Example shown:
2.4mH with single stacks of 15 x counterweights to offer wind speed capability of 16m/s (57.6Kph)h

OUTDOOR HOARDINGS – SINGLE STACK – 'WEIGHT / HEIGHT/ WIND SPEED' EXAMPLES

FREE-STANDING HOARDING OPTIONS FOR **SINGLE STACK OF COUNTERWEIGHTS @ 1.2MW INTERVALS**

SOLID PANEL HEIGHT – MAX (H)	STUD – 90 X 45 (4X2) MPG10	WIND SPEED 10M/S (36KPH)	WIND SPEED 11M/S (39.6KPH)	WIND SPEED 12M/S (43.2KPH)	WIND SPEED 13M/S (46.8KPH)	WIND SPEED 14M/S (50.4KPH)	WIND SPEED 15M/S (54KPH)
1.8m	*90 x 45 MPG10*	*3*	*3*	*4*	*5*	*6*	*7*
2.4m	*90 x 45 MPG10*	*5*	*6*	*8*	*10*	*11*	*13*
3m	*90 x 45 MPG10*	*8*	*10*	*13*	*15*	*18*	*N/A*
3.6m	*90 x 45 MPG10*	*12*	*15*	*19*	*N/A*	*N/A*	*N/A*
4m	*90 x 45 MPG10*	*15*	*19*	*N/A*	*N/A*	*N/A*	*N/A*

FREE-STANDING HOARDING OPTIONS FOR **SINGLE STACK OF COUNTERWEIGHTS @ 0.6MW INTERVALS**

SOLID PANEL HEIGHT – MAX (H)	STUD – 90 X 45 (4X2) MPG10	WIND SPEED 10M/S (36KPH)	WIND SPEED 13M/S (46.8KPH)	WIND SPEED 15M/S (54KPH)	WIND SPEED 19M/S (68.4KPH)	WIND SPEED 21M/S (75.6KPH)	WIND SPEED 23M/S (82.8KPH)
1.8m	*90 x 45 MPG10*	*3*	*3*	*4*	*6*	*8*	*10*
2.4m	*90 x 45 MPG10*	*3*	*5*	*7*	*12*	*14*	*17*
3m	*90 x 45 MPG10*	*4*	*8*	*11*	*18*	*N/A*	*N/A*
3.6m	*90 x 45 MPG10*	*6*	*12*	*16*	*N/A*	*N/A*	*N/A*
4m	*90 x 45 MPG10*	*8*	*14*	*20*	*N/A*	*N/A*	*N/A*

See 'Lomax System Outdoor Configurator' for full range of options

DOUBLE STACK CONFIGURATION

Example shown:
3.6mH with double stacks of 7+7 x counterweights to offer wind speed capability of 15m/s (54Kph)



OUTDOOR HOARDINGS – DOUBLE STACK – 'WEIGHT / HEIGHT/ WIND SPEED' EXAMPLES

FREE-STANDING HOARDING OPTIONS FOR **DOUBLE STACK OF COUNTERWEIGHTS @ 1.2MW INTERVALS**

SOLID PANEL HEIGHT – MAX (H)	STUD – 90 X 45 (4X2) MPG10	WIND SPEED 15M/S (54KPH)	WIND SPEED 19M/S (68.4KPH)	WIND SPEED 21M/S (75.6KPH)	WIND SPEED 23M/S (82.8KPH)	WIND SPEED 26M/S (93.6KPH)	WIND SPEED 29M/S (104.4KPH)
1.8m	*90 x 45 MPG10*	*3+3*	*4+4*	*4+4*	*5+5*	*N/A*	*N/A*
2.4m	*90 x 45 MPG10*	*3+3*	*5+5*	*7+7*	*8+8*	*11+11*	*14+14*
3m	*90 x 45 MPG10*	*5+5*	*9+9*	*11+11*	*13+13*	*17+17*	*N/A*
3.6m	*90 x 45 MPG10*	*7+7*	*12+12*	*16+16*	*19+19*	*N/A*	*N/A*
4m	*90 x 45 MPG10*	*9+9*	*16+16*	*19+19*	*N/A*	*N/A*	*N/A*

FREE-STANDING HOARDING OPTIONS FOR **DOUBLE STACK OF COUNTERWEIGHTS @ 0.6MW INTERVALS**

SOLID PANEL HEIGHT – MAX (H)	STUD – 90 X 45 (4X2) MPG10	WIND SPEED 15M/S (54KPH)	WIND SPEED 19M/S (68.4KPH)	WIND SPEED 21M/S (75.6KPH)	WIND SPEED 23M/S (82.8KPH)	WIND SPEED 26M/S (93.6KPH)	WIND SPEED 29M/S (104.4KPH)
1.8m	*90 x 45 MPG10*	*3+3*	*3+3*	*3+3*	*3+3*	*4+4*	*4+4*
2.4m	*90 x 45 MPG10*	*3+3*	*3+3*	*4+4*	*4+4*	*6+6*	*7+7*
3m	*90 x 45 MPG10*	*3+3*	*5+5*	*6+6*	*7+7*	*9+9*	*11+11*
3.6m	*90 x 45 MPG10*	*4+4*	*6+6*	*8+8*	*10+10*	*13+13*	*16+16*
4m	*90 x 45 MPG10*	*5+5*	*8+8*	*10+10*	*12+12*	*15+15*	*19+19*

See 'Lomax System Outdoor Configurator' for full range of options

For all enquiries, please contact:
1300 0 LOMAX
1300 0 56629
lomaxsystem.com