IMPACT-RATED INDOOR HOARDING

– No fixings required to anything
– No ground penetration
– Compliant to AS4687

FREE-STANDING

Designed and structurally engineered to free-stand up to 8mH using a standard 90 x 45 MPG pine stud – no bracing or fixings required





IMPACT-RATED

Pre-certified and impact tested from both the front and rear of the hoarding for compliance to AS4687

INDOOR HOARDING 'WEIGHT TO HEIGHT' GUIDE FOR COMPLIANCE TO AS4687

SOLID PANEL HEIGHT – MAX (H)	STUD – 90 X 45 (4X2) MPG10	QUANTITY OF COUNTER-WEIGHTS PER STACK	MAX INTERVAL BETWEEN COUNTER-WEIGHT STACKS	CEILING, FLOOR OR SIDE BRACING REQUIREMENTS
1.2m	*90 x 45 MPG10*	*2*	*2.4mW*	*Freestanding - Not Required*
1.8m	*90 x 45 MPG10*	*3*	*1.2mW*	*Freestanding - Not Required*
2.4m	*90 x 45 MPG10*	*3*	*1.2mW*	*Freestanding - Not Required*
3m	*90 x 45 MPG10*	*4*	*1.2mW*	*Freestanding - Not Required*
3.6m	*90 x 45 MPG10*	*4*	*1.2mW*	*Freestanding - Not Required*
4m	*90 x 45 MPG10*	*5*	*1.2mW*	*Freestanding - Not Required*
4.6m	*90 x 45 MPG10*	*6*	*1.2mW*	*Freestanding - Not Required*
5m	*90 x 45 MPG10*	*8*	*1.2mW*	*Freestanding - Not Required*
5.6m	*90 x 45 MPG10*	*10*	*1.2mW*	*Freestanding - Not Required*
6m	*90 x 45 MPG10*	*12*	*1.2mW*	*Freestanding - Not Required*
6.6m	*90 x 45 MPG10*	*16*	*1.2mW*	*Freestanding - Not Required*
7m	*90 x 45 MPG10*	*16*	*1.2mW*	*Freestanding - Not Required*
7.6m	*90 x 45 MPG10*	*20*	*1.2mW*	*Freestanding - Not Required*
8m	*90 x 45 MPG10*	*20*	*1.2mW*	*Freestanding - Not Required*

Lower Cross-Brace and Support Post Required for all Certification – See LOMAX for Technical Guide / Build Process

LOMAX SYSTEM
MODULAR HOARDING SOLUTIONS
COMPACT | REUSABLE | FREESTANDING

For all enquiries, please contact:
1300 0 LOMAX
1300 0 56629
lomaxsystem.com